

Features:

- Sealed With Pure Dow Corning SP4577 Silicone Sealant.
 - Ensuring the best waterproof connection
- 600 Volt Rating
- Industry Leading Dielectric Strength, 50 mil gap volts/mil: >450
- Industry Leading Volume Resistivity at 73°F (23°C): $\text{ohm-cm } 2.17 \times 10^{15}$
- UL 486D Compliant
- Single Step Connection
 - Pre-twisting of wires is not required. One-and-Done is all it takes for a secure waterproof connection



Proudly Made in USA!

We take pride in making 100% of our products right here in the USA. We are committed to manufacturing a top quality product, and at some point we all have to ask ourselves if a product is going into American Soil should it not be made on American Soil?

Installation Instructions:

ALWAYS TURN OFF POWER BEFORE INSTALLING OR REMOVING CONNECTORS. ONLY INSTALL PER LOCAL AND NATIONAL CODES. NOT FOR USE IN CONTINUOUS SUBMERSION APPLICATIONS.

1. Strip wires larger than #16: 1/2", wires smaller than #16 strip 7/16"
2. Pre-twisting of wires is unnecessary. Hold stripped wires with insulation even.
3. Straighten any frayed strands or bent conductors.
4. Firmly push wire into connector and twist connector clockwise onto wire until tight. Do not over-tighten and do not reuse.

TwistN Splice

Pure Silicone Filled Water Proof Wire Connectors



A step up in quality and performance.



www.twistnsplice.com
9331 Douglas Dr.
Riverside, CA 92503
(888) 549-8155