







Twist N Splice

Outdoor Wire Connector Wire Combinations		
Charcoal/White, Suggested Wire Combinations		
2 #14	1 #14 w/1-3#18,20	3 #16 w/1 #18-22
2-5 #18	2 #14 w/1 #18	1 #18 w/1-4 #20
3-5 #20	1 #16 w/1 #18	4 #18 w/1 #20
1 #14 w/1-2 #16	2 #16 w/1-2 #18	4 #20 w/1 #22
Charcoal/Grey, Suggested Wire Combinations		
1-3 #12	2 #14 w/2-4 #16	1 #12 w/1-3 #14
2-4 #14	1 #10 w/1-2 #14	1 #12 w/2-4 #18
2-6 #16	1 #10 w/1-3 #16	1 #14 w/3-4 #18
4 #14 w/1 #18	1 #12 w/1-4 #16	2 #12 w/1 #14
Charcoal/Blue, Suggested Wire Combinations		
2 #8	1 #10 w/3-5 #14	3 #10 w/1-2 #18
2-3 #10	2 #10 w/1-2 #12	4 #12 w/1 #14
3-5 #12	2 #10 w/1-3 #14	1 #10 w/2-3 #12
3 #12 w/1 #14		
Gray/Gray, Suggested Wire Combinations		
2 #14	1 #14 w/1-3#18,20	3 #16 w/1 #18-22
2-5 #18	2 #14 w/1 #18	1 #18 w/1-4 #20
3-5 #20	1 #16 w/1 #18	4 #18 w/1 #20
1 #14 w/1-2 #16	2 #16 w/1-2 #18	4 #20 w/1 #22
Blue/Blue, Suggested Wire Combinations		
2 #14	1 #14 w/1-3#18,20	3 #16 w/1 #18-22
2-5 #18	2 #14 w/1 #18	1 #18 w/1-4 #20
3-5 #20	1 #16 w/1 #18	4 #18 w/1 #20
1 #14 w/1-2 #16	2 #16 w/1-2 #18	4 #20 w/1 #22
Tan, Suggested Wire Combinations		
2 #8	1 #10 w/3-5 #14	3 #10 w/1-2 #18
2-3 #10	2 #10 w/1-2 #12	4 #12 w/1 #14
3-5 #12	2 #10 w/1-3 #14	1 #10 w/2-3 #12
3 #12 w/1 #14		

How To Order:		
Item	Bag Quantity	Part #:
Charcoal/White	50	CW12-22
Charcoal/Grey	50	CG8-22
Charcoal/Blue	50	CB6-14
Gray/Gray	50	GG12-22
Blue/Blue	50	BB12-22
Tan	50	T6-14

 <p>1.100" 0.480"</p>	<p>Charcoal/White</p> <p>0.25" Longer body than leading competitor to accommodate new pre-stripped valve wires</p> <p>Wire Type: Copper/Copper Wire Range: Min #22/Max #12 Temperature Rating: 280°F</p>
 <p>1.300" 0.670"</p>	<p>Charcoal/Gray</p> <p>Wire Type: Copper/Copper Wire Range: Min #22/Max #8 Temperature Rating: 280°F</p>
 <p>1.640" 0.820"</p>	<p>Charcoal/Blue</p> <p>Wire Type: Copper/Copper Wire Range: Min #14/Max #6 Temperature Rating: 280°F</p>
 <p>0.932" 0.539"</p>	<p>Blue/Blue</p> <p>Great for Irrigation and Landscape Lighting applications.</p> <p>Wire Type: Copper/Copper Wire Range: Min #22/Max #12 Temperature Rating: 280°F</p>
 <p>1.640" 0.820"</p>	<p>Tan</p> <p>Great for Irrigation and Landscape Lighting applications.</p> <p>Wire Type: Copper/Copper Wire Range: Min #14/Max #6 Temperature Rating: 280°F</p>
 <p>1.100" 0.480"</p>	<p>Gray/Gray</p> <p>0.25" Longer body than leading competitor to accommodate new pre-stripped valve wires</p> <p>Wire Type: Copper/Copper Wire Range: Min #22/Max #12 Temperature Rating: 280°F</p>